



X-Flow Type G 5W-40

APPLICATION

- Fully synthetic 5W-40 oil suitable for petrol and diesel vehicles including those with fuel injected, multivalved and turbo charged engines.

COMMA RECOMMENDS THIS PRODUCT FOR APPLICATIONS REQUIRING:

MB 229.1; VW 502 00, VW 505 00, RN0700, RN0710
ACEA A3/B4; API SL CF

TYPICAL INSPECTION DATA

Specific gravity at 20°C	0.853
Viscosity @ 100°C	13.5 cSt
Viscosity @ 40°C	78 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	6400 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash	1.2%
Zinc	0.12%
Calcium	0.33%
Phosphorus	0.10%
Colour	Brown
Flash Point	230 °C
Pour Point	-36 °C

HANDLING

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

SHELF LIFE

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.