



X-Flow Type V 5W-30

APPLICATION

- Fully synthetic 5W-30 oil for VW/Audi group petrol and diesel vehicles operating under long life service regimes.
- Low viscosity to give fast oil flow on start up.

COMMA RECOMMENDS THIS PRODUCT FOR APPLICATIONS REQUIRING:

VW 504 00, VW 507 00

TYPICAL INSPECTION DATA:

Specific Gravity at 20°C	0.848
Viscosity @ 100°C	11.7 cSt
Viscosity @ 40°C	70 cSt
Viscosity Index	170
CCS @ -30°C	6300 cP
T.B.N	5.4mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.08%
Calcium	0.15%
Phosphorus	0.07%
Colour	Brown
Flash Point	230 °C
Pour Point	-36 °C

HANDLING

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

SHELF LIFE

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

md 26-10-2012

